VITRUM HOME CONTROL

Datasheet


www.vitrum.com

Vitrum II EU Rolldown Shutters and Curtains Control Wireless

cod. 02E020010

SPEAKS Z-WAVE®





CE

FUNCTIONAL SPECIFICATION

- Two-button for controll of rolldown shutters and curtains
- Touch control with capacitive technology and concave surface for tactile Feedback
- Acoustic feedback signal
- Crown backlit by low-consumption LEDs

COMMAND MODE

- Two capacitive button with " On-Off " contol
  Up - Down or Open - Close

MECHANICAL CHARACTERISTICS

- Fitting Box 503 (wall or plasterboard)
- Dimension 126x95mm
- Depht at sight 8 mm
- Operating temperature: 0-40°C
- Button Diameter 16 mm
- Light ring diameter 20 mm
- Weight: 210 g.

ELECTRICAL CHARACTERISTICS

- Power: 230V
- Energy consumption: < 1W
- Configuration: 3 wires
- Relays 16 A (P.F.=1)
- Output power per channel < 800 VA For electric motor control
- Frequency of communication: F.M. 868.4MHz - R.F radiated power <1mW
- R.F. Range: 20 m. MAX (open field)

Compliant with:

CEI EN 60669-2-1
Compatibility E.M.C.: CEI EN 55015
R&TTE: 1999/5/CE

mpgdstudio.com

THINK SIMPLE™

Think Simple SpA reserves the right to modify its products at any time and without notice in order to better their quality and functionality. Therefore, all the information given in this datasheet is to be considered subject to possible modifications.

Think Simple SpA
CF / P.Iva 01675770935
www.thinksimple.it
info@thinksimple.it
support@thinksimple.it

Head Office
viale Lino Zanussi, 3
33170 Pordenone
Tel +39 0434 516 216
Fax +39 0434 516 230

Sales Office
corso Garibaldi, 86
20121 Milano
Tel +39 02 655 600 29
Fax +39 02 454 982 95